

Supreme 1 Polypropylene Lumber Wrap

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

A high strength, lightweight coated fabric consisting of a reinforcing polypropylene scrim coated with polypropylene on both sides. This product is designed for effective packaging of lumber while in storage and transit

FABRIC SPECIFICATIONS

Color: White/Black, White/Beige, or other colored coatings available
Weight: 100 g/m² (2.95 oz/yd²)*

ROLL SPECIFICATIONS

Cores: 3 inch I.D., 4 inch I.D. or 5 inch I.D. available
Width: Up to 136 inches (-0, +0.5") as ordered
Length: Up to 1800 yds/roll

These values are typical data and are not intended as limiting specifications.

* Subject to change without prior notification



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.565.2000
www.itape.com | info@itape.com

PERFORMANCE PROPERTIES

The following data are typical values based on ASTM standard tests. These data should not be considered specification.

Grab Tensile (N) ASTM D5034	Warp 125 lb (555)/ Weft 115 lb (510)
Tongue Tear (N) ASTM D2261	Warp 35 lb (155)/ Weft 35 lb (155)
Trapezoidal Tear (N) ASTM D4533	Warp 45 lb (199)/ Weft 40 lb (177)
Mullen Burst ASTM D3786	190 psi (1309 kPa)
Pliability	- 40° C or - 40° F
Outdoor Weathering	>80% strength retained after 6 months outdoor exposure

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/20